

MILFORM™

METALFORMING FLUIDS

MILFORM™ 1200

<p>APPLICATIONS</p>	<p>MILFORM™ 1200 is a non-VOC water based, synthetic vanishing oil designed to replace VOC containing vanishing oils, in moderate duty drawing, bending, piercing, blanking, and rolling applications of ferrous and non-ferrous metals.</p>
<p>FEATURES & BENEFITS</p>	<p>GOOD TOOL AND DIE LIFE</p> <p>WATER BASED SYNTHETIC FOR FERROUS AND NON-FERROUS APPLICATIONS</p> <p>EVAPORATES AT ROOM TEMPERATURE AFTER USE, REQUIRING NO POST CLEANING</p> <p>CONTAINS NO VOLATILE ORGANIC COMPOUNDS (VOC'S)</p> <p>WILL NOT STAIN ALUMINUM, COPPER, & BRASS ALLOYS</p> <p>CHLORINE AND SULFUR FREE</p> <p>CLEAN RUNNING, OIL-FREE PRODUCT</p> <p>GOOD CORROSION CONTROL</p>
<p>RECOMMENDED STARTING DILUTIONS</p>	<p>FOR INDUSTRIAL USE ONLY</p> <p>Use between 25% and 100% for stamping and drawing ferrous and some nonferrous metals.</p> <p>MILFORM™ 1200 is to be mixed with water for use (add concentrate to water).</p> <p>Add no other substances to the concentrate or mix unless approved by Technical Services (1-513-841-8133).</p> <p>Not recommended for use with magnesium or alloyed magnesium.</p> <p>For concentration analysis, use the Total Alkalinity or BCG.</p>

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Appearance and odor: Clear/Cherry

Colors available: Undyed

Solubility in water: Complete

Weight, lb/gal, 60°F (15.6°C): 8.6

Specific gravity, (H₂O =1): 1.03

Boiling point, °F (°C): 212 (100)

Flash point, COC, °F (°C): None, self extinguishing

Fire point, COC, °F (°C): NA

Extinguishing media: NA

Unusual fire & explosion hazards: None

Freezing point (or pour point), °F, (°C): 30 (-2)

If frozen, thaw completely at room temperature.

pH, concentrate: 8.9

pH, 25% mix, typical operating conditions: 8.7

Total chlorine/chloride, wt%, calculated: 0.00/<50 ppm

Total sulfur, wt%, calculated: 0.00

Mercurials, phenols, phosphates, PCB's, PTBBA, nitrite, diethanolnitrosamine, chlorinated paraffins, chlorinated solvents, silicones, mineral oil: none.

Available in 5-gallon pails, 55-gallon drums, and bulk containers.

For additional information concerning **MILFORM™ 1200** refer to its OSHA MSDS or contact Technical Services at 1-513-841-8133.

Milacron Consumable Products Division will grant credit on any product which proves defective in material or workmanship, as determined by us, subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the amount of customer use; no credit will be granted for products over one year old as determined by the laboratory control number. These terms do not in any way extend to any product covered by this agreement which has a life, under normal usage, inherently shorter than the one-year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product or part. **NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE SHALL APPLY. LIMITATION OF LIABILITY:** Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages.

Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

Consumable Products Division/Milacron Marketing Company
Cincinnati, Ohio 45209

FS: 12/13/99:1992:327

PC 9845